



NIPNVR064A16NASL

64CH NVR, ADVANCE SERIES, NDAA, NO HDD





Network video recorder (NVR) for 64 IP channels, NDAA compliant, max. resolution 16 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 640 Mbps. Supports all DVA video analysis functions for the connected cameras. Face and number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Alarm inputs/outputs. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. This NVR connects to Comelit servers protected by AWS services.

AWARDS







NIPNVR064A16NASL

| 64CH NVR, ADVANCE SERIES, NDAA, NO HDD | | |
|--|--|--|
| | MAIN FEATURES | |
| Video inputs | | |
| Main video output | 1 HDMI (8K) 2 HDMI (4K) 1 HDMI (Full HD) 1 VGA | |
| Audio Inputs/Outputs | 1/1 | |
| Alarm Inputs/Outputs | 24/8 | |
| Video compression | H.265S / H.265 + / H.265 / H.264 | |
| Playback / recording frame rate | 30fps@16MP | |
| Additional Hard Disks (SATA) | 16 (16x10TB max) | |

| SOFTWARE/FIRMWARE SPECIFICATIONS | |
|--|---|
| Recording methods | Automatic, manual, programmed, event |
| | HDMI 1: 64, HDMI 2: 36, HDMI 3: 16, HDMI 4: 16 |
| Maximum number of channels being played simultaneously | 1@16MP, 4@4K |
| Protocols supported | DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, ONVIF (Profile-T, Profile-S, Profile-G) |
| IP assignment | Manual, DHCP |
| Max bandwidth (Mbps) | 640 |
| Remote control via browser | Internet Explorer, Firefox, Chrome, Safari |
| Remote control by software | Comelit CCTV Manager |
| Remote control by mobile | APP Comelit CCTV |
| Users connected at the same time | 64 |
| Main functions | Video analysis (only with dedicated cameras), Car park management function, Alarm system function, RAID (1, 5, 6, 10) |
| Car plate database [max. number of registrable plates] | 50000 |

| FUNCTIONS | |
|--------------------------|-----|
| Motion detection (zones) | Yes |

HARDWARE SPECIFICATIONS





NIPNVR064A16NASL

64CH NVR, ADVANCE SERIES, NDAA, NO HDD

Type of connections/ports 1xUSB 3.0, 2x eSATA, 2xEthernet 10/100/1000 Mbit/s, 3xUSB 2.0

| | GENERAL DATA |
|---------------------------------|-------------------------------|
| Machine absorption (no HDD) (W) | 50 |
| Supply voltage (VAC) | 100÷240, 50÷60Hz |
| Height (mm) | 143 |
| Width (mm) | 437 |
| Depth (mm) | 483 |
| Product weight (g) | 13500 |
| Type of finishing materials | Metallic |
| Product color | Black |
| Operating temperature (°C) | -10 ÷ 50 |
| Operating humidity (RH max) (%) | 25 ÷ 90 |
| Supplied accessories | Mouse, Rack mounting brackets |