

**Art.-Nr. P607**

- Werkzeuglose Rohreinführung M20 / M25
- Absolut betondicht - sichere Zugentlastung
- Individuelle Einbauöffnungen möglich
- Stabiler Metalldeckel, keine Zusatzbauteile nötig

**Technische Daten****Sonstige Eigenschaften**

Rohrgrößen	2 x M20 o. 2 x M25
Ortbeton	ja
Fertigteilwerke	ja
Sichtbeton	ja (ideal)
Geeignet für NV	ja
Geeignet für HV	ja
Geeignet für LED	ja
Material Deckenausschnitt	Styrodur
Material Dose	Kunststoff
Material Decke	geerdete, verzinkte Metallplatte
EAN	4260182062197
Zolltarifnummer	39259080

Abmessungen & Verpackungen

Durchmesser	310 mm
Tiefe	135 mm
Verpackungseinheit	5 Stück

**Order-no. P607**

- Toolless installation for pipe sizes M20 / M25
- Safe strain relief of the pipes caused by Quick-Fix technology
- Individual cutouts
- No additional components needed

**Technical data****Other characteristics**

Pipe sizes	2 x M20 or 2 x M25
In-situ concrete	yes
Precast factories	yes
Exposed concrete	yes (ideal)
Suitable for low voltage	yes
Suitable for high voltage	yes
Suitable for LED	yes
Material blanket	Styrodur
Material	can plastic
Material ceiling	grounded, galvanized metal plate
EAN	4260182062197
Customer tariff number	39259080

Dimensions & packaging

Diameter	310 mm
Depth	135 mm
Packing unit	5 pieces