



NIPNVR128A16NASL

128CH NVR, ADVANCE SERIES, NDAA, NO HDD





Network video recorder (NVR) for 128 IP channels, NDAA compliant, max. resolution 16 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 768 Mbps. Supports all DVA video analysis functions for the connected cameras. Face and number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Alarm inputs/outputs. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. This NVR connects to Comelit servers protected by AWS services.

AWARDS







NIPNVR128A16NASL

128CH NVR, ADVANCE SERIES, NDAA, NO HDD			
MAIN FEATURES			
Video inputs	128 (16MP/12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF)		
Main video output	1 HDMI (8K) 2 HDMI (4K) 1 HDMI (Full HD) 1 VGA		
Audio Inputs/Outputs	1/1		
Alarm Inputs/Outputs	24/8		
Video compression	H.265S / H.265 + / H.265 / H.264		
Playback / recording frame rate	30fps@16MP		
Additional Hard Disks (SATA)	16 (16x10TB max)		

SOFTWARE/FIRMWARE SPECIFICATIONS		
Recording methods	Automatic, manual, programmed, event	
	HDMI 1: 64, HDMI 2: 36, HDMI 3: 16, HDMI 4: 16	
Maximum number of channels being played simultaneously	1@16MP, 4@4K	
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, ONVIF (Profile-T, Profile-S, Profile-G)	
IP assignment	Manual, DHCP	
Max bandwidth (Mbps)	768	
Remote control via browser	Internet Explorer, Firefox, Chrome, Safari	
Remote control by software	Comelit CCTV Manager	
Remote control by mobile	APP Comelit CCTV	
Users connected at the same time	64	
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function, RAID (1, 5, 6, 10)	
Car plate database [max. number of registrable plates]	50000	

FUNCTIONS





NIPNVR128A16NASL

128CH NVR, ADVANCE SERIES, NDAA, NO HDD

Motion detection (zones) Yes

HARDWARE SPECIFICATIONS			
Type of connections/ports	1xUSB 3.0, 2x eSATA, 2xEthernet 10/100/1000 Mbit/s, 3xUSB 2.0		

	GENERAL DATA
Machine absorption (no HDD) (W)	50
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	143
Width (mm)	437
Depth (mm)	483
Product weight (g)	13500
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Mouse, Rack mounting brackets