



**KAE5064**

## **EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT**



The kit includes: four Mini series door-entry phones art. 2702W, a transformer art. 1200, an Extra series external unit designed for 2/4 call buttons art. ET5100, 4 single buttons for Extra entrance panel art. ET9211. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the corresponding accessories supplied with the kit.

### **AWARDS**





**KAE5064**

## EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

### PRODUCTS IN THE KIT



**ET5100 EXTRA 4+N ENTRANCE PANEL PREPARED FOR 2/4 BUTTONS**

Extra series audio entrance panel with stainless steel cover and nameplate backlighting. To be completed with single button art. ET9211 (pack of 4 units) to offer 4 call buttons, or with double-height button art. ET9210 (pack of 2 units) to offer 2 call buttons. The entrance panel can be surface-mounted or flush-mounted using the relevant accessories supplied. Traditional 4 + N wiring system. Dimensions (W x H x D): 95x165x6.5 mm (flush) - 25 mm (surface).

GENERAL DATA	
Type	Monoblock
Flush-mounted	Yes
Wall-mounted	Yes



**KAE5064**

**EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT**



**2702W 2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL**

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light.  
Dimensions: 105x191x28 mm

GENERAL DATA	
Height (mm)	190
Width (mm)	105
Depth (mm)	28
Product color	White
Type of finishing materials	Plastic
Product weight (g)	260
Wall-mounted	Yes
Desk base-mounted	Yes

COMPATIBLE SYSTEMS	
Traditional system	Yes

AUDIO FEATURES	
Microphone	4mm (Ø), Omnidirectional
Loudspeaker	0.50mm, 0.5W

ELECTRICAL CHARACTERISTICS	
Supply voltage	15÷16VDC
Absorption in stand-by (W)	3
Maximum absorption (W)	6

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release



**KAE5064**

## EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

### HARDWARE FEATURES

Clamps	S 2 3 4 P1 P2
Total buttons (n°)	2

### ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

### GENERAL FEATURES

Door opener	Yes
Silent mode (Privacy)	Yes
Ringtone volume control	Yes
Electronic bell	Yes



**KAE5064**

## EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



**1200 TRANSFORMER 10VA 0-230V/0-12V**

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES	
Supply voltage	230 VAC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9
GENERAL DATA	
Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finishing materials	Plastic
Operating temperature (°C)	-5 ÷ 40
COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum power delivered (W)	15



**KAE5064**

## EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

### ACCESSORIES



**ET9151 Flush-mounted box for Extra entrance panel**

Flush-mounted box for Extra series external unit art. ET5200.  
Dimensions 164.5x93.5x25 mm.



**ET9161 Wall bracket for Extra entrance panel**

Wall housing for Extra series external unit art. 5200. Dimensions  
94x164x19 mm.



**1229 EXTENSION SOUNDER**

Additional bell for call repetition can be controlled directly from  
terminals S- and S+ of the brackets and/or from the telephones.  
Surfacemounted or on civil series 503 box. Dimensions: 110X75X29  
mm.