

**Art.-Nr. PK01**

- 5 x 16 mm² oder max. 22 mm Durchmesser
- Einfache Montage, absolut dicht
- Universal Abdichtung für Strom-, Tel-, LWL- und Wasserleitungen
- Geteilte Ausführung, auch wenn schon Leitungen verlegt sind kann die Abdichtung montiert werden

**Technische Daten****Sonstige Eigenschaften**

Druckwasserdicht	1 bar - geprüft
Aushärtezeit	20 - 30 Minuten
EAN	4260182060377
Zolltarifnummer	39259080

Abmessungen & Verpackungen

Durchmesser Bohrloch	35 mm
Verpackungseinheit	1 Set

Lieferumfang

- Spezialabdichtmörtel im Eimer
- 2 Stück Hauseinführungen (bestehend aus 2 x 2 Hälften)
- 1 Messbecher

**Order-no. PK01**

- 5 x 16 mm² or max. 22 mm diameter
- Easy installation, absolutely leakproof
- Universal sealing for power, telecom, fiber optic and water pipes
- Splitted design, even if pipes were already layed the sealing can be mounted

**Technical data****Other characteristics**

Pressure water tight	1 bar - tested
Curing time	20 - 30 minutes
EAN	4260182060377
Customer tariff number	39259080

Dimensions & packaging

Diameter borehole	35 mm
Packing unit	1 set

Scope of delivery

- Special sealing mortar in the bucket
- 2 pieces house inlets (consisting of 2 x 2 halves)
- 1 measuring cup