



NIPNVR032A12NASL

32CH NVR, ADVANCE SERIES, NDAA, NO HDD





Network video recorder (NVR) for 32 IP channels, NDAA compliant. Max. resolution 12 MP, video compression H.265S/H.265+/H.265/H.264, dual streaming, bandwidth 320Mbps. Supports all DVA video analysis functions for the connected cameras. Face and number plate database. Compatible with browsers: IE/Google Chrome/Edge/Firefox/Safari. Alarm inputs/outputs. Remote control via Comelit CCTV APP and Comelit CCTV Manager software. This NVR connects to Comelit servers protected by AWS services.

AWARDS





NIPNVR032A12NASL

32CH NVR, ADVANCE SERIES, NDAA, NO HDD

	MAIN FEATURES
Video inputs	32 (12MP/8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/ 720P/960H/D1/CIF)
Main video output	1 HDMI (4K) 1 VGA (1920x1080)
Audio Inputs/Outputs	1/1
Alarm Inputs/Outputs	16/4
Video compression	H.265S / H.265+ / H.265 / H.264
Playback / recording frame rate	30fps@8MP 20fps@12MP
Additional Hard Disks (SATA)	8 (8x10TB max)

SOFTWARE/FIRMWARE SPECIFICATIONS	
Recording methods	Automatic, manual, programmed, event
Maximum number of channels being played simultaneously	1@12MP, 4@Full HD
Protocols supported	DDNS, DHCP, HTTP, HTTPS, SMTP, TCP/IP, ONVIF (Profile-T, Profile-S, Profile-G)
IP assignment	Manual, DHCP
Max bandwidth (Mbps)	320
Remote control via browser	Internet Explorer, Firefox, Chrome, Safari
Remote control by software	Comelit CCTV Manager
Remote control by mobile	APP Comelit CCTV
Users connected at the same time	64
Main functions	Video analysis (only with dedicated cameras), Car park management function, Alarm system function, RAID (1, 5, 6, 10)

FUNCTIONS		
Motion detection (zones)	Yes	
HARDWARE SPECIFICATIONS		
Type of connections/ports	2xUSB 2.0, 1xUSB 3.0, 1x eSATA, 2xEthernet 10/100/1000 Mbit/s	

The technical specifications are subject to change without prior notice.



NIPNVR032A12NASL

32CH NVR, ADVANCE SERIES, NDAA, NO HDD

	GENERAL DATA
(W)	30
Supply voltage (VAC)	100÷240, 50÷60Hz
Height (mm)	90
Width (mm)	436
Depth (mm)	445
Product weight (g)	7400
Type of finishing materials	Metallic
Product color	Black
Operating temperature (°C)	-10 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 90
Supplied accessories	Power supply, Mouse, Rack mounting brackets